



STANDARD FEATURES ALASKAN

EFFECTIVE SEPTEMBER 1, 2015

WWW.HEWESCRAFT.COM

	240	260
Anodes: Installed on port transducer bracket	standard	standard
Bilge Pumps: Two bilge pumps; one auto, one manual	standard	standard
Bow Eye: Double, welded	standard	standard
Bow Deck: Welded treadplate, self-bailing	standard	standard
Bow Rails: 12" welded	standard	standard
Cleats: 8", welded, eight on gunwales, one on bow inwale	9	9
Cup Holders: Two on port-side dash	standard	standard
Decals: 15" vinyl side striping with graphics; black, white, blue, yellow, green, red, orange, charcoal	standard	standard
Door: Bulkhead, locking with fixed window	standard	standard
Fish Box: 40 gallon in transom with cutting board lid	standard	standard
Fish Box: In floor, with macerator pump	standard	standard
Fuel System: 127 gallon	standard	standard
Glove Box: Lockable	standard	standard
Grab Handles: Bulkhead, glove box, windshield, interior shelves, aft cabin sides	standard	standard
Horn: Flush mount	standard	standard
Instrument Panel:	standard	standard
- Ten water-resistant rocker style switches		
- Power point		
- Twelve-gang expansion fuse block		
Lights: LED, navigational	standard	standard
Lights: LED, anchor, removable, cabin top with storage clips	standard	standard
Lights: LED, two overhead interior cabin	standard	standard
Line Locker: Bow, treadplate hatch, line notch	standard	standard
Paint: Light gray, full inside	standard	standard
Rails: Cabin top, 4", aluminum	standard	standard
Steering: SeaStar hydraulic	standard	standard
Steering Wheel: Stainless steel with rubber grip	standard	standard
Stern Eyes: Welded, port and starboard	standard	standard
Storage: Dry seat boxes with lid	standard	standard
Storage: Two trays aft of bulkhead, port and starboard	standard	standard
Storage: Lockable cabinets aft of bulkhead, port and starboard (single helm only)	standard	standard
Storage: Hinged treadplate step between consoles	standard	standard
Storage: Nets, removable, under console	standard	standard
Storage: Shelves inside cabin	standard	standard
Transducer Bracket: Port and starboard	standard	standard
Transom: Extended, for twin 25"-shaft or single 30"-shaft engine(s) (no kicker step)	standard	standard
Trim Tabs: Electric 12"x12" with LED indicator	standard	standard
Windows: Screened, sliding side windows	standard	standard
Windshield Wiper: Port and starboard	standard	standard





AVAILABLE OPTIONS ALASKAN

EFFECTIVE SEPTEMBER 1, 2015

WWW.HEWESCRAFT.COM

Anchor Pulpit: Plain (weld-on or bolt-on)

Anchor Pulpit: Large stainless steel roller (weld-on or bolt-on)

Anchor Pulpit: Large stainless steel roller and capstan winch (weld-on or bolt-on)

Anchor Roller: Welded, aluminum 5/8" max rope diameter

Battery Selector Switch: One with dual trays, not-wired

Battery Selector Switch: Two with dual trays, not-wired

Cabin Configurations: 8 different styles – regular-length and medium-length cabins

Canvas: Privacy curtain (with port 42" sleeper seat)

Decals: 15" decal; black, white, blue, yellow, green, red, orange, charcoal

Downrigger Brackets: Low profile, stand-alone

Downrigger Brackets: Plates (available with stern rails only)

Floor: Diamond treadplate, aft of bulkhead

Fuel Line Pickup: Additional for trolling motor

Fuel system: 156 gallon (260 only)

Fuel/Water Separator: Single or twin (standard with Yamaha pre-rig)

Galley Table: Removable

Heater: Cabin interior

Light: LED, on fishing deck, mounted to cabin top

Lights: LED courtesy, two at transom and one at console

Livewell: Fish box upgrade

Paint: Half- or full-side; red, black, white, blue, yellow, green

Pre-Rig: Yamaha or Honda - single or twin

Rooftop Radar/Accessories Arch: Bolt-on

Rod Holder: Rocket launchers, eight station mounted to cabin top

Seat: High-back, side storage box, bellows suspension, swivel, and slide

Seat: Truck seat, heavy-duty suspension with swivel, port or starboard

Seat: Arm rests, pair for one high-back seat, port or starboard

Seat: Slide port or starboard

Sharkhide Oxidation Fighter

Steering: Second console station, hydraulic, on bulkhead

Stern Rails: 27" or 40" aluminum

Swim Ladder: Port or starboard

Wash-Down System (Standard With Head)