



STANDARD FEATURES OPEN FISHERMAN

EFFECTIVE SEPTEMBER 1, 2015

WWW.HEWESCRAFT.COM

	160	180	200
Bilge Pump: Single bilge pump with auto switch	standard	standard	standard
Bow Eye: Double, welded	standard	standard	standard
Bow Deck: Treadplate	standard	standard	standard
Cleats: 8", four on gunwales, one on bow inwale	5	5	5
Decals: 15" vinyl side striping with graphics; black, white, blue, yellow, green, red, orange, charcoal	standard	standard	standard
Fish Box: 27 gallon in bow floor, diamond treadplate hatch	standard	standard	standard
Fish Box: 20 gallon in floor, removable, with handle (N/A with center console on 16')	standard	standard	standard
Fuel System: 24 gallon	standard	standard	standard
Fuel Tank Cover: Treadplate	standard	standard	standard
Grab Handle: Starboard side, aft**	standard	standard	standard
Instrument Panel			
- Five water-resistant rocker switches			
- Fuel gauge	standard	standard	standard
- Power point			
- Six-gang expansion fuse block			
Lights: LED, navigational, in bow	standard	standard	standard
Lights: LED, anchor, removable	standard	standard	standard
Paint: Light gray, full inside	standard	standard	standard
Rod Grippers: Inwale, port and starboard	standard	standard	standard
Stern Eyes: Welded, port and starboard	standard	standard	standard
Storage Tray: Port and starboard	standard	standard	standard
Transducer Bracket: Port and starboard	standard	standard	standard
Transom: 20" -shaft main engine and 20" -shaft kicker	standard	standard	standard

**CANADIAN DEALERS: Additional grab handles are required for 160 OF (qty-2) and 180 OF (qty-4) to meet Transport Canada capacity requirements.





AVAILABLE OPTIONS

OPEN FISHERMAN

EFFECTIVE SEPTEMBER 1, 2015

WWW.HEWESCRAFT.COM

Anchor Roller: Welded, aluminum, 5/8" max rope diameter

Anodes: Installed on port transducer bracket

Bow Rails: 5" aluminum

Carpet: Inwale, gray

Center Console: With steering and instrument panel

Center Console: Add windshield and grab rail

Center Console: Add front seat assembly (omits fish box on 16')

Downrigger Brackets: Low profile, stand-alone

Downrigger Brackets: Plates (available with stern rails only)

Grab Handles: On gunwales at motorwell, port and starboard

Lights: LED courtesy, two at transom

Livewell: Bow fish box upgrade

Paint: Half-or full-side; red, black, white, blue, yellow, green

Pre-Rig: Side mount control, multi-function gauge (Honda, Yamaha, Mercury) (with center console only)

Seat: High-back, with swivel and quad base

Seat: Pedestal, high-back with post and base installed, indicate location

Seat: Pedestal base, additional installed, indicate location

Seat: Cushions, pair at motor well

Steering: Baystar, 150HP or less (with center console only)

Stern Rails: 27" or 40" aluminum

Swim Ladder: With platform port or starboard

Transom: 25" -shaft main engine and 20" -shaft kicker

Transom: 27" -shaft jet engine with delta pad and 20" -shaft kicker (180 and 200 only)

Wash-Down System