



EFFECTIVE SEPTEMBER 1, 2015

WWW.HEWESCRAFT.COM

	PV	PV with SLC
Bilge Pump: Single bilge pump with auto switch	standard	standard
Bow Eye: Double, welded	standard	standard
Bow Deck: Treadplate, self-bailing, with storage	standard	standard
Bow Rails: 12" aluminum	N/A	standard
Canvas: Fish curtain; black, blue, green, gray	optional	standard
Cleats: 8" welded	5	7
Cup Holders: Port and starboard	standard	standard
Decals: 15" vinyl side striping with graphics; black, white, blue, yellow, green, red, orange, charcoal	standard	standard
Door: Walk through, access to bow, 2 latches, one top and one bottom	standard	standard
Fish Box: 26 gallon in bow floor	standard	standard
Fuel System: 48 gallons	standard	standard
Glove Box: Lockable	standard	standard
Grab Handles: Inwale front port side, glove box and windshield	standard	N/A
Handrails: Vertical, aft cabin sides	N/A	standard
Horn: Flush mount	standard	standard
Instrument Panel:		
- Six water-resistant rocker style switches	standard	
- Fuel gauge and one panel knock-out for additional gauge		standard
- Power point		
- Six-gang expansion fuse block		
Light: LED, interior, overhead	N/A	standard
Lights: LED, navigational	standard	standard
Lights: LED, anchor, removable	standard	standard
Paint: Light gray, full inside	standard	standard
Rail: Cabin top	N/A	standard
Rod Grippers: Inwale, port and starboard	standard	standard
Seat: High-back, dry box with lid, horseshoe suspension	standard	standard
Steering: No-feedback	standard	standard
Steering Wheel: Stainless steel with rubber grip	standard	standard
Stern Eyes: Welded, port and starboard	standard	standard
Storage Trays: Port and starboard	standard	standard
Storage Trays: Overhead, port and starboard	N/A	standard
Transducer Bracket: Port and starboard	standard	standard
Transom: 25" -shaft main engine and 20" -shaft kicker	standard	standard
Wave Board: At motorwell	standard	standard
Windows: Sliding, port and starboard	N/A	standard
Wipers: Port and starboard	optional	standard





EFFECTIVE SEPTEMBER 1, 2015

WWW.HEWESCRAFT.COM

Anchor Roller: Welded, aluminum, 5/8" max rope diameter
Anodes: Installed on port transducer bracket
Battery Selector Switch: One switch with dual trays, not-wired
Bow Rails: 5" or 12" aluminum
Canvas: Deluxe three bow, with or without top windows
Canvas: Stern cover (available with soft top only)
Canvas Colors: Black, blue, green, gray
Carpet: Inwale, gray
Downrigger Brackets: Low profile, stand-alone
Downrigger Brackets: Plates (available with stern rails only)
Fuel Line Pickup: Additional for trolling motor
Grab Handles: On gunwales at motorwell, port and starboard
Lights: LED courtesy, two at transom and one at console
Livewell: Bow fish box upgrade
Paint: Half- or full-side; red, black, white, blue, yellow, green
Pre-Rig: Yamaha, Honda, Mercury
Seat: High-back, side storage box, bellows suspension, swivel, and slide
Seat: Short jump, pair, 21" storage boxes
Seat: Long jump, 37", storage boxes (available with long canvas or SLC only)
Seat: Sleeper, pair, 42", portside commode cutout (available with long canvas only)
Seat: Pedestal, high-back with post and base installed, indicate location
Seat: Pedestal base, additional installed, indicate location
Seat: Slide port or starboard
Steering: Hydraulic, Baystar, 150HP or less
Steering: Hydraulic, SeaStar for 150HP or more
Stern Rails: 27" or 40" aluminum (40" with soft top only)
Swim Ladder: With platform port or starboard
Trim Tabs: Electric, 9" x 12", with LED indicator lights
Trolling Motor Power Point: At bow (wired to aft battery storage area)
Wash-Down System
Windshield Side Windows: Short window wing, port and starboard (soft top only)
Windshield Wiper: Port, starboard, or both (standard on SLC)